

# COBRA

MODELS: M40B M40SPB M46B M46SPB

## COBRA LAWN MOWER OWNER'S MANUAL



**Cobra Garden Machinery**

Henton and Chattell Ltd., London Road, Nottingham NG2 3HW UK

[www.cobragarden.co.uk](http://www.cobragarden.co.uk)

# CONTENTS

SECTION 1 SYMBOLS MARKED ON THE PRODUCT.....	3
SECTION 2 GENERAL SAFETY RULES.....	3-5
SECTION 3 PARTS DESCRIPTION.....	5-9
SECTION 4 TECHNICAL DATA.....	9-10
SECTION 5 ASSEMBLY.....	10-13
SECTION 6 3 IN 1.....	13-14
SECTION 7 OPERATION INSTRUCTIONS .....	14-18
SECTION 8 MAINTENANCE INSTRUCTIONS.....	18
SECTION 9 LUBRICATION.....	19
SECTION 10 CLEANING.....	19-20
SECTION 11 STORAGE INSTRUCTIONS (OFF SEASON).....	20-21
SECTION 12 TROUBLESHOOTING.....	21
SECTION 13 WARRANTY.....	22
SECTION 14 ENVIRONMENT.....	22
SECTION 15 EC-DECLARATION OF CONFORMITY.....	22-23

**! WARNING:**

For your own safety please read this manual before attempting to operate your new mower. Failure to follow instructions can result in serious personal injury. Spend a few moments to familiarise yourself with your mower before each use.

**1. SYMBOLS MARKED ON THE PRODUCT**



Fig. A

B.1 Read Operator's Manual.

B.2 Keep bystanders away.

B.3 Pay attention to the operator's hands and feet to avoid injury.

B.4 Fuel is flammable, keep fire away. Do not add fuel with running machine.

B.5 Toxic fumes; don't operate indoors, including your garage or shed.

B.6 When mowing, please wear protective glasses and ear plugs to defend the operator himself.

B.7 When repairing, please remove the spark plug, before undertaking repair work according to the operational manual.

B.8 Caution: Engine hot.



Figure B: Safety Label Found On Lawn Mower: KEEP HANDS AND FEET AWAY.

**2. GENERAL SAFETY RULES**

**! WARNING:** When using petrol tools, basic safety precautions, including the following, should always be followed to reduce the risk of serious personal injury and/or damage to the unit. Read all these instruction before operating this product and retain these instructions for future reference.

**! WARNING:** This machine produces an electromagnetic field during operation. This field may under some circumstances interfere with active or passive medical implants. To reduce the risk of serious or fatal injury, we recommend persons with medical implants to consult their physician and the medical implant manufacturer before operating this machine.

## **Training**

1. Before using the lawnmower read the instructions carefully. Familiarise yourself with the controls and pay particular attention in learning how to stop the machine in an emergency.
2. Never allow children or people unfamiliar with these instructions to use the lawn mower. Local regulations can restrict the age of the operator.
3. Never mow while people, especially children or pets are nearby.
4. Never use the mower if the operator is taking medicine or substances that could affect or impair his ability to react or concentrate.
5. Keep in mind that the operator or user is responsible for accidents or hazards occurring to other people or their property.

## **Before you start**

1. While mowing, always wear substantial footwear and long trousers. Do not operate the equipment when barefoot or wearing open toed sandals.
2. Thoroughly inspect the area where the equipment is to be used and remove all objects which can damage or be thrown by the machine.
3. **WARNING** - Petrol is highly flammable.
  - Store fuel in containers specifically designed for this purpose.
  - Refuel outdoors only and do not smoke while refuelling; add fuel before starting the engine.
  - Never remove the cap of the fuel tank or add petrol while the engine is running or when the engine is hot.
  - If petrol is spilled, do not attempt to start the engine, but move the machine away from the area of spillage and avoid creating any source of ignition until petrol vapours have dissipated.
  - Replace all fuel tank and container caps securely.
4. Replace faulty silencers.
5. Before using, always visually inspect to see that the blade, blade bolts and cutter assembly are not worn or damaged. Replace worn or damaged blades and bolts in sets to preserve balance.

## **Operation and Caution**

1. Do not operate the engine in a confined space where dangerous carbon monoxide fumes can collect, refuel outdoors only.
2. Mow only in daylight or in good artificial light.
3. Avoid operating the equipment in wet grass, where feasible.
4. Always be sure of your footing on slopes.
5. Walk, never run, always be in control of the lawnmower and never allow yourself to be pulled along.
6. For wheeled rotary machines, mow across the face of slopes, never up and down.
7. Exercise extreme caution when changing direction on slopes.
8. Do not mow excessively steep slopes of more 20°
9. Use extreme caution when reversing or pulling the lawn mower towards you.
10. Stop the blade if the lawn mower has to be tilted for transportation when crossing surfaces other than grass, and when transporting the lawn mower to and from the area to be mowed
11. Never operate the lawn mower with defective guards, or without safety devices, for example deflectors and/or grass catchers, in place.
12. Do not change the engine governor settings or over speed the engine.
13. Before starting the engine disengage all blades and drive clutches.
14. Keep your feet well away from the blade when starting the engine and in accordance with the instructions.
15. Do not tilt the lawn mower when starting the engine and always start on a flat surface free from long grass.

16. Do not start the engine when standing in front of the discharge chute.
17. Never put hands or feet near or under rotating parts. Keep clear of the discharge opening at all times.
18. Always ensure the engine is fully switched off before picking up/carrying the Lawnmower.
19. Stop the engine and disconnect the spark plug wire, make sure that all moving parts have come to a complete stop and, where a key is fitted remove the key, make sure engine has had time to cool.
  - Before unclogging chute and clearing blockages.
  - Before checking, cleaning or working on the lawn mower.
  - After striking a foreign object. Inspect the lawnmower for damage and make repairs before restarting.
  - If the lawn mower starts to vibrate abnormally (check immediately).
20. Stop the engine and disconnect the spark plug wire, make sure that all moving parts have come to a complete stop and, where a key is fitted remove the key, make sure engine is completely cooled.
  - Whenever you leave the lawn mower.
  - Before refuelling.
21. Reduce the throttle setting during engine shut down and, if the engine is provided with a shut-off valve, turn the fuel valve off at the conclusion of mowing.

### **Maintenance and Storage**

1. Keep all nuts, bolts and screws tight to be sure the equipment is in safe working condition.
2. Never store the equipment with petrol in the tank inside a building where fuel vapours can reach an open flame or spark or where the temperature is high.
3. Before storage allow the engine to cool.
4. To reduce the fire hazard, keep the engine, silencer, battery compartment and petrol storage area free of grass, leaves, or excessive grease.
5. Check the grass catcher and deflector frequently for wear or deterioration.
6. Replace worn or damaged parts for safety. Genuine parts should always be used as parts of inferior quality can damage the equipment and compromise safety.
7. If the fuel tank has to be drained, this should be done outdoors. Always ensure engine is completely cooled before starting this task.
8. If the blade needs to be removed, wear strong gloves to prevent injury to hands and fingers. Check the blades balance after sharpening.
9. When transporting the machine make sure you close the fuel cut off. Be careful to ensure weight is evenly distributed. Wear strong gloves.
10. When tilting the machine never tilt towards the air filter as this may become damaged with fuel.
11. Never crank the engine when the spark plug is removed.
12. Frequently check the fuel lines and fittings for damage and cracks, replace if necessary
13. Never start the engine with the air filter cover removed.
14. Carefully clean the mower and grass bag after use to remove debris as this can damage and corrode.

### **Fertilisers and top dressings are particularly corrosive.**

15. In time your chassis may peel because of the abrasive action of the debris making contact. This can be remedied by touching up paintwork where necessary to prevent corrosion.



**Warning: Do not touch rotating blade.**



**Warning: Refuel in a well ventilated area with the engine stopped.**

### 3. PARTS DESCRIPTION




Fig.1

- |                          |                           |                           |                 |
|--------------------------|---------------------------|---------------------------|-----------------|
| 1. Upper handle          | 2. Self-drive Lever (SPB) | 3. Starter handle         | 4. Rope Guide   |
| 5. Locking Lever         | 6. Grass catcher          | 7. Height adjusting lever | 8. Oil cap      |
| 9. Deck                  | 10. Spark plug            | 11. Fuel cap              | 12. Cable clamp |
| 13. Throttle choke Lever | 14. Brake control handle  |                           |                 |

#### Including

A: Spark plug wrench

### 4. TECHNICAL DATA

Model	M40B	M40SPB	M46B	M46SPB
Engine type	Briggs 450E	Briggs 450E	Briggs 450E	Briggs 500E
Self Propelled	No	Yes	No	Yes
Engine Displacement	125 cm <sup>3</sup>	125 cm <sup>3</sup>	125 cm <sup>3</sup>	140 cm <sup>3</sup>
Blade Width	400 mm	400 mm	460 mm	460 mm
Rated Speed	2800/min	2800/min	2800/min	2800/min
Fuel Tank Capacity	0.75L	0.75L	0.75L	0.75L
Grass catcher capacity	50 L	50 L	60 L	60 L
Net Weight	24 kg	26 kg	25.6 kg	28.3 kg
Height adjustment :	25-75mm, 10 adjustment			

Guaranteed Sound pressure level at the operator's position (According to EN 836 Annex H & EN ISO 4871)	85.1 dB(A) (K=3dB(A))
Measured sound power level	93.5 dB(A) K=1.91dB(A)
Guaranteed Sound Power level (According to 2000/14/EC)	96 dB(A)
Vibration (According to EN 836 Annex G)	Max.6.38m/s <sup>2</sup> K=1.5 m/s <sup>2</sup>

## 5. ASSEMBLY

### 5.1 FOLDING HANDLE

1. Fix the lower handlebars into the unit body with a suitable spanner. (Fig.2F)
2. Lift the two locking levers to release the upper handlebars for folding.
3. Push the locking lever closed or tighten the knobs to lock the handlebars in the operating position. (Fig.2G/Fig.2H)
4. Adjust the tension by turning the lock nut with a suitable spanner.
5. Attach the cable-clamp to the position shown and then attach the cable. (Fig.2I)




Fig.2F




Fig.2G




Fig.2H




Fig.2I

### 5.2 MOUNTING AND DISMOUNTING THE GRASS CATCHER

- a) To fit: Raise the rear cover and hitch the grass catcher on rear of mower. (Fig. 3G/3H)
- b) To remove: grasp and lift the rear cover, remove grass catcher. (Fig. 3G/3H)



Fig.3G




Fig.3H

### 5.3 STARTER HANDLE

Move the starter handle from the engine to the rope guide.



Fig.4

### 5.4 HEIGHT OF CUT

Apply outward pressure to disengage lever from rack. Move lever forward or back to adjust height. (see clause 7.9)



Fig.5C

## 7. OPERATING INSTRUCTIONS

### 7.1 BEFORE STARTING

Service the engine with petrol and oil as instructed in the separate engine manual packed with your mower. Read instructions carefully.

 **WARNING!** Petrol is highly flammable.

Store fuel in containers specifically designed for this purpose. Refuel outdoors only, do not smoke while refueling or handling fuel. Never remove the cap of the fuel tank or add petrol while the engine is running or when the engine is hot. If petrol is spilled, do not attempt to start the engine but move the machine away from the area of spillage and avoid creating any source of ignition until petrol vapours have dissipated. Replace all fuel tanks and container caps securely.

Before tipping the lawn mower to maintain the blade or drain oil, remove fuel from tank.

 **WARNING:** never fill fuel tank indoors, with engine running or until the engine has been allowed to cool for at least 15 minutes after running.

## 7.2 TO START ENGINE AND ENGAGE BLADE

**-Always check the engine oil level before starting. Refer to the engine manual.**

1. The unit is equipped with a rubber boot over the end of the spark plug, make certain the metal loop on the end of the spark plug wire (inside the rubber boot) is fastened securely over the metal tip on the spark plug.
2. When starting cool, press the primer bulb 3-5 times before starting the engine. (Fig.8A)
3. Cold engine starting: Turn the throttle choke lever to “” position, full speed. When starting a warm engine, turn the throttle choke lever to the middle position. (Fig.8B)
4. Standing behind the mower, grasp the brake control handle and hold it against the upper handle as shown in Fig.8C.
5. Hold the starter handle as shown Fig.8C and pull up rapidly. Return it slowly to the rope guide bolt after engine starts.

**Release the brake control handle to stop the engine and blade.**



Fig.8A




Fig.8B



Fig. 8C

-  Start the engine carefully according to instructions and with feet well away from the blade.
-  Do not tilt the lawn mower when starting the engine. Start the mower on a level surface, free of high grass or obstacles.
-  Keep hands and feet away from the rotating parts. Do not start the engine when standing in front of the discharge opening.

## 7.3 OPERATION PROCEDURES

During operation, tightly hold the stop control handle with both hands.

-  **Note:** During operation, when the brake control handle is released, the engine will stop and thus stopping the lawnmower from operating.

## 7.4 TO STOP ENGINE

-  **CAUTION:** The blade continues to rotate for a few seconds after the engine is shut off.

1. Release the brake control handle to stop the engine and blade.
2. Disconnect and ground the spark plug wire as instructed in the separate engine manual to prevent accidental starting while equipment is unattended.




Fig.9

## 7.5 USING THE POWER DRIVE FUNCTION (M40SPB & M46SPB) – Self Propelled Mowers Only

Grip the Self-drive control handle, the lawnmower will move forward automatically with a speed of about 3.6 km/h.

Release the self-drive handle and the lawnmower will stop moving.




Fig.10



**CAUTION:** your mower is designed to cut normal residential grass of a height no more than 250mm. Do not attempt to mow through unusually tall dry or wet grass (e.g., pasture) or piles of dry leaves. Debris may build up on the mower deck or contact the engine exhaust presenting a potential fire hazard.

## 7.6 FOR THE BEST RESULTS WHEN MOWING

**Clear lawn of debris:** Be sure that the lawn is clear of stones, sticks, wire or other objects, which could be accidentally thrown out by the mower in any direction and cause serious injury to the operator and others as well as damage to property and surrounding objects.

**Avoid cutting wet grass:** For effective mowing do not cut wet grass, because it tends to stick to the underside of the deck preventing proper mowing of the grass clippings.

**General Recommendations:** Cut no more than 1/3 the length of the grass. The recommended cut for mowing is 1/3 the length of the grass. Ground speed will need to be adjusted so the clippings can be dispersed evenly into the lawn. For especially heavy cutting in thick grass it may be necessary to use one of the slowest speeds in order to get a clean well mowed cut. When mowing long grass you may have to cut the lawn in two passes, lowering the blade another 1/3 of the length for the second cut and perhaps cutting in a different pattern than was used the first time. Overlapping the cut a little on each pass will also help to clean up any stray clippings left on the lawn. The mower should always be operated at full throttle to get the best cut and allow it to do the most effective job of mowing.

**Clean underside of deck:** Be certain to clean the underside of the cutting deck after each use to avoid a build-up of grass, which would prevent proper mulching. Mowing leaves. The mowing of leaves can also be beneficial to your lawn. When mowing leaves make sure they are dry and are not laying too thick on the lawn. Do not wait for all the leaves to be off the trees before you mow.



**WARNING:** if the mower blade strikes a foreign object, then stop the engine. Remove the wire from spark plug, thoroughly inspect the mower for any damage and repair the damage before restarting and operating the mower. Extensive vibration of the mower during operation is an indication of serious damage. The unit should be promptly inspected and repaired.

## 7.7 GRASS CATCHER



**IMPORTANT:**

If the grass catcher is full of grass, you will need to empty and clean the grass catcher, make sure it is clean and ensure its meshwork is ventilated.




Fig.11E




Fig.11F

## 7.8 DECK

The underside of the mower deck should be cleaned after each use to prevent a buildup of grass clippings, leaves, dirt or other matter. If this debris is allowed to accumulate, it will invite rust and corrosion, and may prevent proper mulching. The deck may be cleaned by tilting the mower and scraping clean with a suitable tool (make certain the spark plug wire is disconnected).

## 7.9 HEIGHT ADJUSTMENT INSTRUCTIONS



**CAUTION:** Do not at any time make any adjustment to lawnmower without first stopping the engine and disconnecting the spark plug wire. Your mower is equipped with a central height adjustment lever offering 10 height positions. (Fig.12E)

The height (the blade to the ground) can be adjusted from 25 mm to 75 mm.

1. Stop mower and disconnect spark plug cable before changing mower cutting height.
2. The central height adjustment lever offers you 10 different height positions.

To change the height of cut, squeeze the adjuster lever towards the wheel, moving up or down to selected height.



Fig.12E

## 8. MAINTENANCE INSTRUCTIONS

### SPARK PLUG

Use only original replacement spark plugs. For best results, replace the spark plug every 100 hours of use.

## 9. LUBRICATION INSTRUCTIONS



**CAUTION:** DISCONNECT SPARK PLUG BEFORE SERVICING.

1. WHEELS-Lubricate the ball bearings in each wheel at least once a season with a light oil.
2. ENGINE-Follow engine manual for lubrication instructions.

## 10. CLEANING



**CAUTION:** Do not hose the engine. Water can damage engine or contaminate the fuel system.

1. Wipe deck with a dry cloth.
2. Hose under deck by tilting the mower so that the spark plug is up.

### 10.1 ENGINE AIR CLEANER



**CAUTION:** Do not allow dirt or dust to clog the air filter foam element.

The engine air cleaner element must be serviced (cleaned) after 25 hours normal mowing. The foam element must be serviced regularly if the mower is used in dry dusty conditions.

#### TO CLEAN THE AIR FILTER

1. Lift the tabs on top of the filter cover.
2. Remove the filter cover.
3. Wash filter element in soapy water. **DO NOT USE PETROL!**

4. Air dry filter the element.
5. Place a few drops of SAE30 oil on the foam filter and squeeze tightly to remove any excess oil.
6. Reinstall filter.

**!** NOTE: Replace the filter, if it is frayed, torn, damaged or unable to be cleaned.



Fig.13A




Fig.13B




Fig.13C

## 10.2 CUTTING BLADE

**!** CAUTION: Be sure to disconnect and ground the spark plug wire before working on the cutting blade to prevent accidental engine starting. Protect hands by using heavy gloves or a rag to grasp the cutting blades.

Tip mower as specified in separate engine manual. Remove the hex bolt and washer, which holds the blade and blade adapter to the engine crankshaft. Remove the blade and adapter from the crankshaft.

**!** WARNING: Periodically inspect the blade adapter for cracks, especially if you strike a foreign object. Replace when necessary. For best results your blade should be sharp. Slightly worn blades may be re-sharpened with care. After removing the blade, it may be ground or filed, so that the cutting edge is as close to the original bevel as possible. It is extremely important that each cutting edge receives an equal amount of grinding to prevent an unbalanced blade. Improper blade balance will result in excessive vibration causing damage to the engine and mower. Be sure to carefully balance blade after sharpening. The blade can be tested for balance by balancing it on a round shaft screwdriver. Remove metal from the heavy side, until it balances evenly.

Before reassembling the blade and the blade adapter to the unit, lubricate the engine crankshaft and the inner surface of the blade adapter with light oil. Install the blade adapter on the crankshaft. Refer Fig.14. Place the blade with the part number facing away from the adapter. Align the washer over the blade and insert the hex bolt. Tighten the hex bolt to the torque listed below:




Fig.14

## 10.3 BLADE MOUNTING TORQUE

Center Bolt 40Nm.min, 50Nm.max. To insure safe operation of your unit. All nuts and bolts must be checked periodically for correct tightness. After prolonged use, especially in sandy soil conditions, the blade will become worn and lose some of the original shape. Cutting efficiently will be reduced and the blade should be replaced. Replace with an approved factory replacement blade only. Possible damage resulting from blade unbalance is not the responsibility of the manufacturer.

When you change the blade, use the original type marked on the blade:

Cobra part number 26300100401 for M40B and M40SPB

Cobra part number 263001465 for M46B and M46SPB

Please contact your local dealer for the supply of genuine Cobra parts

**!** WARNING: Do not touch rotating blade.

## 10.4 ENGINE

Refer to the separate engine manual for engine maintenance instructions.

Maintain engine oil as instructed in the separate engine manual packed with your unit.

### **Read and follow the engine instructions carefully.**

Service the air filter as per the separate engine manual. Clean every few hours under extremely dusty conditions. Poor engine performance and flooding usually indicates that the air filter requires attention. To service the air filter, refer to the separate engine manual packed with your mower. The spark plug should be cleaned and the gap reset annually. Spark plug replacement is recommended at the start of each mowing season. Check the engine manual for the correct plug type and gap specifications. Clean the engine regularly with a cloth or brush. Keep the cooling system (blower housing area) clean to permit proper air circulation, which is essential to engine performance. Be certain to remove all grass, dirt and combustible debris from the muffler area.

## 11. STORAGE INSTRUCTIONS (OFF SEASON)

The following steps should be taken to prepare the lawn mower for storage at the end of the mowing season.

1. Drain the fuel from the engine by running the engine until it stops.
  - a) Start the engine and let it run until it has used up all remaining petrol and stalls.
  - b) Remove the spark plug. Use an oilcan to fill approx. 20 ml oil into the combustion chamber. Operate the starter to evenly distribute the oil in the combustion chamber. Replace the spark plug.
2. Clean and grease the lawnmower carefully as described above under "Lubrication".
3. Slightly grease the cutter to avoid corrosion.
4. Store the lawnmower in a dry, clean and frost-protected place.



**CAUTION!** The engine must have completely cooled down before storing the lawnmower.



**NOTE:** - When storing any type of power equipment in an unventilated or material storage shed,

-Care should be taken to rust-proof the equipment. Using a light oil or silicone, coat the equipment, especially cables and all moving parts.

- Be careful not to bend or kink cables.

- If the starter rope becomes disconnected from rope guide on the handle, disconnect and ground the spark plug wire. Depress the blade control handle and pull the starter rope out from the engine slowly. Slip the starter rope into the rope guide bolt on the handle.

### **Transport**

Turn the engine off. Ensure not to bend or damage the cutter when pushing the lawnmower over obstacles.

## 12. TROUBLESHOOTING

PROBLEM	PROBABLE CAUSE	CORRECTIVE ACTION
Engine does not start.	Throttle choke not in the correct position for the prevailing conditions.	Move throttle choke to the correct position
	Fuel tank is empty.	Fill the tank with fuel: refer to the ENGINE MANUAL.
	Air filter element is dirty.	Clean air filter element: refer to the ENGINE MANUAL
	Spark plug loose.	Tighten spark plug to 25-30Nm.
	Spark plug wire loose or disconnected from plug.	Install spark plug wire on spark plug.
	Spark plug gap is incorrect.	Set gap between electrodes at 0.7 to 0.8mm
	Spark plug is defective	Install new, correctly gapped plug: refer to the ENGINE OWNERS MANUAL
	Carburetor is flooded with fuel	Remove air filter element and pull starter rope continuously until the carburetor clears itself and then install the air filter element.
	Faulty ignition module	Contact the service agent.
Engine difficult to start or loses power.	Dirt, water, or stale fuel tank.	Drain fuel and clean tank. Fill tank with clean, fresh fuel
	Vent hole in fuel tank cap is plugged.	Clean or replace fuel tank cap.
	Air filter element is dirty.	Clean air filter element.
Engine operates erratically.	Spark plug is defective.	Install new, correctly gapped plug: refer to the ENGINE OWNERS MANUAL
	Spark plug gap is incorrect.	Set gap between electrodes at 0.7 to 0.8mm
	Air filter element is dirty.	Clean air filter element: refer to the ENGINE OWNERS MANUAL
Engine idles poorly.	Air filter element is dirty.	Clean air filter element: refer to the ENGINE OWNERS MANUAL
	Air slots in engine shroud are blocked.	Remove debris from slots.
	Cooling fins and air passages under engine blower housing are blocked.	Remove debris from cooling fins and air passages.
Engine skips at high speed.	Gap between electrodes of spark plug are too close.	Set gap between electrodes at 0.7 to 0.8mm
Engine overheats	Cooling air flow is restricted.	Remove any debris from slots in shroud, blower housing, and air passages
	Incorrect spark plug.	Install QC12YC spark plug and cooling fins on engine
Mower vibrates abnormally	Cutting assembly is loose.	Tighten blade
	Cutting assembly is unbalanced	Balance or replace the blade

## **12. WARRANTY**

This product is warranted in accordance with legal regulations for a 24 month period effective from the date of purchase by the first user.

This product will not be covered if used in a commercial application.

This warranty covers all material or production failures, it does not include: defects from normal wear and tear, parts such as, bearings, brushes, cables, air cleaning elements, brake pad, clutch disc, tyre, wheel, recoil starter rope, belts, cutter blades, plugs, lubricant oils and grease or accessories. Damage or defects resulting from abuse, accidents or alterations, natural fading of painted or plated surfaces, sheet peeling and other natural deterioration.

Any damage that occurs from the use of non-genuine Cobra parts will not be covered.

We reserve the right to reject any claim where the purchase cannot be verified or when it is clear that the product was not maintained properly. (Clean ventilation slots, carbon brushes and serviced regularly)

Expenses incidental to the warranty claim that are not covered;

-Compensation for loss of time, commercial loss or rental costs of substitute product.

-Costs incurred for transportation to and from the dealership.

Any damage that occurs from the following will not be covered; exposure of the product to smoke and soot, chemical agents, bird droppings or other animal waste, seawater, sea breeze, salt or other environmental phenomena.

Any damage resulting from operating methods other than those indicated in the owner's manual will not be covered.

Your purchase receipt must be kept as proof for date of purchase. Your un-dismantled mower must be returned to your dealer in an acceptably clean state, accompanied by your proof of purchase.

### **Please Register Your Mower**

If your dealer did not collect registration information from you, please take a few minutes and register your purchase with Cobra.

You can register by completing and mailing the registration card that should be in the box or by going online to [www.cobragarden.co.uk](http://www.cobragarden.co.uk) and clicking on Product Registration.

Before using the lawn mower, all mower operators must read this manual

## **13. ENVIRONMENT**

Should your machine need replacement after extended use, do not put it in the domestic waste but dispose of it in an environmentally safe way.



### 15. EC Declaration of Conformity

<b>EC Declaration of Conformity</b>	
We herewith declare,	Cobra Garden Machinery Henton & Chattell Ltd, London Road, Nottingham NG2 3HW United Kingdom
that the following machine complies with the appropriate basic safety and health requirements of the EC Directive based on its design and type, as brought into circulation by us.	
In case of alteration of the machine, not agreed upon by us, this declaration will lose its validity	
Machine Description:	Lawn Mower
Machine Types:	M40B (1563N) M40SPB (1564N) M46B (1565N) M46SPB (1566N)
Displacement:	125 cm <sup>3</sup>
Max. Cutting length:	400 mm - M40B (1563N) M40SPB (1564N) 460 mm - M46B (1565N) M46SPB (1566N)
Measured sound power level	93.5 dB(A)
Guaranteed sound power level:	96 dB(A) Notified Body for EC Directive 2000/14/EC:0036 TüV Süd Industrie Service GmbH Westendstrasse 199 . 80686 München . Deutschland
Applicable EC Directives:	EC Machinery Directive: 2006/42/EC EC Directive of Electromagnetic Compatibility 2004/108/EC EC Directive of noise emission 2000/14/EC EC Directive of engine emission 97/68/EC
Applicable Harmonized Standards:	EN 836 EN ISO 14982
Authorised Signature/Date/ Place:	 Peter J. Chaloner 02-12-2013
Title of Signatory:	Managing Director
name and address of the person authorized to compile the technical file	Cobra Garden Machinery Henton & Chattell Ltd, London Road, Nottingham NG2 3HW United Kingdom