




SPECIFICATIONS

ENGINE		LT1 NS96
Engine type	Cub Cadet OHV	
Engine displacement	439 cm ³	
Rated power	9.0 kW / 2,800 min ⁻¹	
Cylinders	Single	
Tank volume (capacity)	3.8 l	
DRIVE SYSTEM		
Transmission	Transmatic	
DISCHARGE SYSTEM		
Bag (capacity)/accessory no	200 l Optional/(OEM-190-180A)	
Bag lever/hardtop	-/-	
Bag full indicator/grass deflector	-/Standard	
Turning circle	46 cm/18"	
CUTTING SYSTEM		
Mowing area in m ² /h	4,000	
Cutting width	96 cm/36"	
Cutting height (min.-max.)	30-95 mm	
Deck engagement	Manual lever control	
Deck height positions	5 positions	
Wash nozzle/Mulch Kit	-/(OEM-190A116)	
DIMENSIONS		
LpA/LwA/LwAg (dB)	88/98/100	
Vibration value body/K-factor	1 / 0.5 m/s ²	
Vibration value hand/arm/K-factor	5 / 1.5 m/s ²	
Dimensions (L/W/H)	170 cm / 107 cm / 100 cm	
Net weight	150 kg	
Model number	13AB76DF603	



COMFORTABLE SEAT WITH HIGH BACKREST
The high backrest supports an upright posture, making it far more comfortable.



TRANSMATIC TRANSMISSION
Shifting without stopping: Easy selection of drive direction and speed.



CUTTING HEIGHT ADJUSTMENT
5-position height adjustment to easily change the cutting height (30-95 mm).



STEEL FRAME
All tractor frames are made of fully welded and powder-coated rugged steel for added durability.

